

Sure-Tough ST 8015

APPLIED POLYMER SOLUTIONS, LLC

PRODUCT PROFILE

GENERIC DESCRIPTION **Bio-Degradable Degreaser** - Sure-Tough ST 8015 is a heavy duty cleaner, non-foaming cleaner formulated for versatility and dependability. Worker safety is an integral part of the manufacturing process and this product contains no caustics, butyl ethers, or chlorinated and petroleum based solvents. Unlike many industrial strength cleaners, ST 8015 is 100% biodegradable and environmentally safe. The versatility of this product is enhanced by complete water reducibility to assure the capability to customize the cleaning strength to meet your specific needs. ST 8015 is a concentrated non-flammable detergent that dissolves a wide range of greases and oil based soils while leaving the area with a refreshing citrus scent. Terpene hydrocarbons, the major component of oranges, and naturally occurring, are used in this product. As a water reducible cleaner, the ability to work with and around most metals is assured by the addition of flash rust additives and inhibitors. This product is compatible with most industrial coatings including epoxies and urethanes.

RECOMMENDED FOR ST 8015 uses can encompass anything from floor cleaning to hot dip tank cleaning in the following industries:

AUTOMOTIVE SERVICE & TRUCKING FLEETS
STEEL MILLS
MANUFACTURERS
FOUNDRIES
METAL FABRICATORS

PRINTING PLANTS
CONTRACT CLEANING FIRMS
U.S. POST OFFICES
WASTE CLEAN UP FIRMS
MILITARY INSTALLATIONS

DIRECTIONS FOR USE

For heavy duty cleaning and degreasing, we recommend 1 part ST 8015 to 4 parts water by volume. Deviations from this ratio can employ differing concentrations suited to the cleaning strength needed. For less soiled floors, dilute with more water and for heavily soiled floors, dilute with less water. Ratios varying from 1:1 to 50:1 (Water:ST 8015) can be used for cleaning.

APPLICATION PROCEDURE

For cleaning- dilute ST 8015 to the desired strength and apply to the surface with a mopping action.. Allow the solution to remain on the floor for approximately five minutes. Remove the loosened grime and dirt by mopping and then rinse the floor with clean water. For walls

Warranty & Limitations of Seller's Liability: Applied Polymer Solutions, LLC warrants only that our materials represented herein meet the formulation standards or Applied Polymer Solutions, LLC.

We warrant that our products are manufactured to the specifications and that the information stated here is accurate to the best of our knowledge. Information supplied about our products is not a representation or a warranty. It is supplied on the condition that the buyer shall conduct their own tests to determine the suitability of our product for their particular purpose. Listed physical properties are typical and should not be construed as specifications. **NO WARRANTY IS MADE, EXPRESSED OR IMPLIED, REGARDING SUCH OTHER INFORMATION, THE DATA ON WHICH IT IS BASED, OR THE RESULTS THAT WILL BE OBTAINED FROM ITS USE. NO WARRANTY IS MADE, EXPRESSED OR IMPLIED, THAT OUR PRODUCT SHALL BE MERCHANTABLE OR THAT OUR PRODUCT SHALL BE FIT FOR ANY PARTICULAR PURPOSE. NO WARRANTY IS MADE THAT THE USE OF SUCH INFORMATION OR OUR PRODUCT WILL NOT INFRINGE UPON ANY PATENT.** We have no liability for incidental or consequential damages, direct or indirect. Our liability is limited to the net selling price of our product or the replacement of our product, at our option. Acceptance of product delivery means acceptance of the terms of this warranty whether or not purchase orders or other documents state terms that vary from this warranty. No representative is authorized to make any representation or warranty or assume any other liability on our behalf with any sale of our products. Our products contain chemicals that may **CAUSE SERIOUS PHYSICAL INJURY. BEFORE USING, READ THE MATERIAL SAFETY DATA SHEET AND FOLLOW ALL DIRECTIONS AND PRECAUTIONS ACCORDINGLY.**

APPLIED POLYMER SOLUTIONS, LLC

507 Five Leaf Lane, Waxhaw, NC 28173

866-592-9858

<http://applied-polymer-solutions.com>